

\*FASTUS is a product brand of OPTEX FA.

## IO-Link Supported BGS Sensor

# Z4B Series



### Features

- IO-Link supported: Connectable to various field networks via IO-Link Master
- High power and small spot LED light source
- Enhanced ambient illuminance resistance

### Lineup

Type	Appearance	Sensing distance	Model (Models in parentheses are connector types)	
			NPN type	PNP type
BGS		5 to 80 mm (20 to 80 mm)	<b>Z4B-S08N</b> (Z4B-S08CN4)	<b>Z4B-S08P</b> (Z4B-S08CP4)
		5 to 100 mm (20 to 100 mm)	<b>Z4B-10N</b> (Z4B-10CN4)	<b>Z4B-10P</b> (Z4B-10CP4)
		10 to 300 mm (50 to 300 mm)	<b>Z4B-30N</b> (Z4B-30CN4)	<b>Z4B-30P</b> (Z4B-30CP4)

• For the connector type, purchase an optional connector cable.

### Accessories

#### M8 connector cables

Model	Description
<b>M84CN-2S</b>	Straight, 2 m
<b>M84CN-5S</b>	Straight, 5 m
<b>M84CN-10S</b>	Straight, 10 m
<b>M84CN-2L</b>	L-shaped, 2 m
<b>M84CN-5L</b>	L-shaped, 5 m
<b>M84CN-10L</b>	L-shaped, 10 m

#### Mounting brackets

Model	Description
<b>BEF-W100-B</b>	For cable type, Floor mounted
<b>BEF-W100-A</b>	For connector type, Back-mounted
<b>BEF-W100-C</b>	For cable type, Floor mounted

#### Protective mounting brackets

Model	Description
<b>LK-S01</b>	Floor mounted
<b>LK-S02</b>	Wall mounted

- Mounting bracket is not included. Purchase as necessary.
- For the connector type, purchase an optional connector cable.
- For IO-Link connection with USB adapter and master unit, use 3rd party product in the market.

# Specifications

Type		BGS			
Model	NPN	Cable	Z4B-S08N	Z4B-10N	Z4B-30N
		Connector	Z4B-S08CN4	Z4B-10CN4	Z4B-30CN4
	PNP	Cable	Z4B-S08P	Z4B-10P	Z4B-30P
		Connector	Z4B-S08CP4	Z4B-10CP4	Z4B-30CP4
Sensing distance*			5 to 80 mm	5 to 100 mm	10 to 300 mm
Adjustable distance range*			20 to 80 mm	20 to 100 mm	50 to 300 mm
Light source			Red LED		
Spot size			Approx. Ø 2.5 mm at 60 mm	Approx. Ø 10 mm at 100 mm	Approx. Ø 30 mm at 300 mm
Response time			Light ON setting: No light received → Light received; 1 ms or less, Light received → No light received; 3.5 ms or less Dark ON setting: Light received → No light received; 3.5 ms or less, No light received → Light received; 1 ms or less		
Hysteresis*			Max. 3 %	Max. 3 %	Max. 5 %
Sensitivity adjustment			6-turn potentiometer (endless)		4-turn potentiometer (endless)
Indicators			Output indicator (orange LED), Stability indicator (green LED)		
Control output			NPN/PNP Open collector 100 mA/30 VDC Max. (Residual voltage 1.8 V Max.)		
Output mode			Light ON, Dark ON selectable by switch		
IO-Link specifications			Ver. 1.1, Baud rate: COM3 (230.4 kbps), Number of process input data bytes: 2 bytes, Minimum cycle time: 0.5 ms		
Connection			Cable type: 2 m long, Ø 3.8 mm (Minimum bending radius: 15.2 mm (When fixed in place)) Connector type: M8 4-pin		
Rating	Supply voltage		IO-Link mode: 18 to 30 VDC, SIO mode: 10 to 30 VDC including 10 % ripple (p-p)		
	Current consumption		30 mA or less		
Applicable regulations	EMC		EMC directive (2014/30/EU)		
	Environment		RoHS directive (2011/65/EU), China RoHS (MIIT Order No. 32)		
Applicable standards			EN 60947-5-2		
Company standards			Noise resistance: Feilen Level 3 cleared		
Environmental resistance	Ambient temperature/humidity		-25 to 55°C/35 to 85 %RH (No condensation or freezing)		
	Ambient illuminance		Sunlight: 50,000 lx or less, Incandescent lamp: 5,000 lx or less		
	Storage temperature/humidity		-40 to 70°C/35 to 95 %RH (No condensation or freezing)		
	Vibration resistance		10 to 55 Hz, Double amplitude 1.5 mm, 2 hours in each of the X,Y and Z directions		
	Shock resistance		Approx. 100 G (1000 m/s <sup>2</sup> ) 3 times in each of the X,Y and Z directions		
Degree of protection			IP67		
Material			Housing: ABS, Front Cover: PMMA		
Weight without cable			Approx. 10 g		
Included items			Instruction manual		

\*White paper 100 mm × 100 mm


• Specifications are subject to change without prior notice. Thank you for your understanding.

## Dimensions


(Unit: mm)

## Circuit diagram


### [Cable type]




### [Connector type]




### [NPN mode]




### [PNP mode]



### [IO-Link mode]



### [M8 connector pin layout]



Never use these products as sensing devices for personnel protection.

Doing so could lead to serious injury or death.

Before use please read an instruction manual.

• Specifications are subject to change without prior notice.



**OPTEX**  
**FA**

**OPTEX FA CO., LTD.** [www.optex-fa.com](http://www.optex-fa.com)

**Japan** OPTEX FA Co., Ltd. Kyoto +81-75-325-1314 faovs@optex-fa.com  
**China** Guangzhou OPTEX Co., Ltd. Guangzhou, Guangdong +86-20-39922102 sales\_ofc@optex-fa.cn  
**Thailand** OPTEX (Thailand) Co., Ltd. Bangkok +66-2-168-3162 thailand@optex-fa.com  
**U.S.A.** OPTEX FA Inc. Schaumburg, Illinois +1-847-565-3500 ofi-sales@optex-fa.com