


FVDK 12

sample drawing



general data

actual range Sb (FSE 200C1002)	320 mm
sensing distance Tw (FUE 200C1003)	90 mm
light source	pulsed red LED
light indicator	LED green
alignment / soiled lens indicator	LED green, flashing
output indicator	LED yellow
adjustment	Teach-in
wave length	660 nm

electrical data

response time / release time	< 1 ms
voltage supply range +Vs	10 ... 30 VDC
current consumption max. (no load)	46 mA
current consumption typ.	36 mA
voltage drop Vd	< 1,8 VDC
output function	light / dark operate switchable
output current	< 100 mA
short circuit protection	yes
reverse polarity protection	yes

mechanical data

width / diameter	12 mm
height / length	33,2 mm
depth	60 mm
type	rectangular
housing material	PBT / PC

ambient conditions

operating temperature	-25 ... +55 °C
protection class	IP 65

sample picture



FVDK 12

order reference	min. output pulse length	output circuit	connection types	version
FVDK 12N6101/S35A	-	NPN	connector M8 4 pin	-
FVDK 12N6401/S35A	-	NPN	connector M8 4 pin	integrated alarm output
FVDK 12P6101	-	PNP	cable, 2 m	-
FVDK 12P6101/S35A	-	PNP	connector M8 4 pin	-
FVDK 12P6401	-	PNP	cable, 2 m	integrated alarm output
FVDK 12P6401/S35A	-	PNP	connector M8 4 pin	integrated alarm output
FVDK 12P6501/S35A	40 ms	PNP	connector M8 4 pin	integrated alarm output