



## HMA I-LIFT 65

530XX-XXXXX-XXXXXX



The height adjustable industrial suspension arm with full integration in the suspension systems HMA I-080, HMA I-130 and HMA I-225

- Default colours
  - Cover: RAL 7035 (Light grey)
  - Bearings: RAL 7016 (Anthracite grey)
  - Special colours on request
- Vertical swivel angle  $\pm 40^\circ$  ( $\pm 210\text{mm}$ ) with continuously variable stroke limiter to  $\pm 0^\circ$
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Hubarretierung mit Bedienerfreigabe (Option)
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Load range exclusive vertical tube and attachments
- Integrated brake
- Low maintenance

<b>Lift length</b>	635 mm	895 mm
<b>Dead weight</b>	18 kg	20 kg
<b>Cable duct</b>	45 x 30 mm	
<b>Vertical stroke</b>	500 mm	900 mm
<b>Loading weight range</b>	0 - 0 kg	0 - 0 kg

## HMA I-LIFT 65-1 (635 MM)

5302X-71XXX-XXXXXXX



Der höhenverstellbare Industrietragarm von 5 – 65 kg mit 635 mm Liftlänge, anschließbar über Kopflager HMA I-080 unten

- Vertical swivel angle +/- 40° (+/-210mm) with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Hubarretierung mit Bedienerfreigabe (Option)
- Vollintegration in die Tragarmsysteme HMA I-080, HMA I-130 und HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Eigengewicht: 18 kg

Product code	Description
53021-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53021-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53022-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53022-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53023-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53023-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53024-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53024-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53025-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53025-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53026-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53026-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53027-71100-8707110	HMA I-Lift 65-1, 635 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53027-71200-8707110	HMA I-Lift 65-1, 635 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

## HMA I-LIFT 65-2 (635 MM)

5302X-72XXX-XXXXXXX



Der höhenverstellbare Industrietragarm von 5 – 65 kg mit 635 mm Liftlänge, anschließbar über Kopflager HMA I-080 oben

- Vertical swivel angle +/- 40° (+/-210mm) with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Hubarretierung mit Bedienerfreigabe (Option)
- Vollintegration in die Tragarmsysteme HMA I-080, HMA I-130 und HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Eigengewicht: 18 kg

Product code	Description
53021-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53021-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53022-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53022-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53023-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53023-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53024-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53024-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53025-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53025-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53026-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53026-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53027-72100-8707110	HMA I-Lift 65-2, 635 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53027-72200-8707110	HMA I-Lift 65-2, 635 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

## HMA I-LIFT 65-1 (895 MM)

5305X-71XXX-XXXXXXX



Der höhenverstellbare Industrietragarm von 5 – 65 kg mit 895 mm Liftlänge, anschließbar über Kopflager HMA I-080 unten

- Vertical swivel angle +/- 40° (+/-210mm) with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Hubarretierung mit Bedienerfreigabe (Option)
- Vollintegration in die Tragarmsysteme HMA I-080, HMA I-130 und HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Eigengewicht: 20 kg

Product code	Description
53051-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53051-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53052-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53052-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53053-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53053-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53054-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53054-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53055-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53055-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53056-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53056-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53057-71100-8707110	HMA I-Lift 65-1, 895 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53057-71200-8707110	HMA I-Lift 65-1, 895 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035

## HMA I-LIFT 65-2 (895 MM)

5305X-72XXX-XXXXXXX



Der höhenverstellbare Industrietragarm von 5 – 65 kg mit 895 mm Liftlänge, anschließbar über Kopflager HMA I-080 oben

- Vertical swivel angle +/- 40° (+/-210mm) with continuously variable stroke limiter to +/- 0°
- Restraint-guided load suspension at head joint
- Head bearing mounting upwards and downwards possible
- Hubarretierung mit Bedienerfreigabe (Option)
- Vollintegration in die Tragarmsysteme HMA I-080, HMA I-130 und HMA I-225
- Loading weight from head joint 5-65 kg in 7 weight ranges (TLB)
- Fine adjustment within the load capacity range (TLB) continuously
- Integrated brake
- Eigengewicht: 20 kg

Product code	Description
53051-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 5-10 kg, Colours: RAL 7016, RAL 7035
53051-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 5-10 kg, lockable, Colours: RAL 7016, RAL 7035
53052-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 9-14 kg, Colours: RAL 7016, RAL 7035
53052-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 9-14 kg, lockable, Colours: RAL 7016, RAL 7035
53053-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 13-20 kg, Colours: RAL 7016, RAL 7035
53053-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 13-20 kg, lockable, Colours: RAL 7016, RAL 7035
53054-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 19-27 kg, Colours: RAL 7016, RAL 7035
53054-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 19-27 kg, lockable, Colours: RAL 7016, RAL 7035
53055-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 26-37 kg, Colours: RAL 7016, RAL 7035
53055-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 26-37 kg, lockable, Colours: RAL 7016, RAL 7035
53056-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 36-52 kg, Colours: RAL 7016, RAL 7035
53056-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 36-52 kg, lockable, Colours: RAL 7016, RAL 7035
53057-72100-8707110	HMA I-Lift 65-2, 895 mm, TLB 51-65 kg, Colours: RAL 7016, RAL 7035
53057-72200-8707110	HMA I-Lift 65-2, 895 mm, TLB 51-65 kg, lockable, Colours: RAL 7016, RAL 7035