

Metal cylindrically shaped inductive sensors **LIR18X** series



Features

- ◆ Extended sensing distance
- ◆ ASIC design, safe and reliable
- ◆ Perfect choice for metallic target detection




Part number

NPN NO	LIR18XBF08DNOY	LIR18XBN12DNOY	PNP NO	LIR18XBF08DPOY	LIR18XBN12DPOY
NPN NC	LIR18XBF08DNCY	LIR18XBN12DNCY	PNP NC	LIR18XBF08DPCY	LIR18XBN12DPCY
NPN NO+NC	LIR18XBF08DNRY	LIR18XBN12DNRY	PNP NO+NC	LIR18XBF08DPRY	LIR18XBN12DPRY

Technical specifications

Mounting	Quasi -flush	Non-flush	Current consumption	≤15mA	
Rated distance [Sn]	8mm	12mm	Circuit protection	Short-circuit, overload and reverse polarity	
Assured distance [Sa]	0...6.4mm	0...9.6mm	Output indicator	Yellow LED	
Dimensions	M18*51.5mm	M18*63.5 mm	Ambient temperature	-25°C...70°C	
Output	NO/NC (depends on part number)		Ambient humidity	35-95%RH	
Supply voltage	10...30 VDC		Switching frequency [F]	400 Hz	200 Hz
Standard target	Fe 24*24*1t	Fe 36*36*1t	Dielectric strength	1000V/AC 50/60Hz 60S	
Switch-point drifts [%/Sr]	≤±10%		Insulation resistance	≥50MΩ (500VDC)	
Hysteresis range [%/Sr]	1...20%		Vibration resistance	10...50Hz (1.5mm)	
Repeat accuracy [R]	≤3%		Degree of protection	IP67	
Load current	≤200mA		Housing material	Nickel-copper alloy	
Residual voltage	≤2.5V		Connection type	2m PVC cable	

Dimensions



Wiring diagram

