

Part Number: 1300170004

Product Description: Mini-Change Field Attachable, Female Connector, 3 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads

Status : Active

Engineering Number: 1A3000-34

Series Number: 130017

Product Category: Circular Industrial

Connectors

Documents & Resources

Drawings

Drawing 1300170004_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Circular Industrial Connectors |
| Series | 130017 |
| Description | Mini-Change Field Attachable, Female Connector, 3 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads |
| Approvals | cCSAus certified |
| IP Rating | IP67 |
| Product Family | Brad Mini-Change Connectors |
| Product Name | Mini-Change |
| Туре | Field Attachable Connector |
| UPC | 78172553098 |

Agency

| CSA | LR6837 |
|-----|--------|
|-----|--------|

Electrical

| Current - Maximum per Contact | 13.0A |
|-------------------------------|------------|
| Voltage - Maximum | 600V AC/DC |

Physical

| Cable Diameter | 5.08-11.43mm (.200450") |
|---------------------------|-------------------------|
| Coupling Type | Internal Thread |
| Diagnostics / LEDs | No |
| Diagnostics Port | No |
| Gender | Female |
| Keyway | Single |
| Material - Connector Body | Nylon |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Net Weight | 68.400/g |
| | |

| Orientation | Straight |
|-------------------------------|----------------|
| Poles | 3 |
| Temperature Range - Operating | -20°C to +80°C |
| Wire Size (AWG) | 15 to 24 |

This document was generated on Jul 16, 2024