

Part Number : 1200650960

Product Description : Micro-Change (M12) Single-Ended Cordset, 8 Poles, Female (90°) to Pigtail, 0.25mm² PUR/PVC Cable, 2.0m (6.56')

Length

Series Number: 120065 Status: Active

Product Category: Circular Industrial Engineering Number: 808001P02M020

Cordsets

Documents & Resources

Drawings

Drawing 1200650960_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Circular Industrial Cordsets |
| Series | 120065 |
| Description | Micro-Change (M12) Single-Ended Cordset, 8 Poles, Female (90°) to Pigtail, 0.25mm² PUR/PVC Cable, 2.0m (6.56') Length |
| IP Rating | IP67 |
| Product Family | Brad Micro-Change (M12) Connectors |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | Europe |
| Type | Single Ended |
| UPC | 78172553723 |

Electrical

| Current - Maximum per Contact | 2.0A |
|-------------------------------|------|
| Voltage - Maximum | 30V |

Physical

| Cable Diameter | 6.70mm (.264") |
|---------------------------|---------------------|
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | PUR/PVC |
| Material - Connector Body | PUR |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |

| Material - O-Ring | Fluoro-elastomer |
|-------------------------------|------------------|
| Material - Plating Mating | Gold |
| Net Weight | 141.254/g |
| Orientation | 90° to Pigtail |
| Poles | 8 |
| Temperature Range - Operating | -30° TO +80°C |
| Wire/Cable Type | EU Cable |
| Wire Size (AWG) | N/A |

This document was generated on Jul 16, 2024