

Part Number : 1200652158

Series Number : 120065 Product Category : Circular Industrial Cordsets Product Description : Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm² PUR/PVC Cable, 10.0m (32.81') Length Status : Active Engineering Number : 805006P03M100

Documents & Resources

Drawings

Drawing 1200652158_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---------------------------------------------------|
| China RoHS | 6 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Category | Circular Industrial Cordsets |
| Series | 120065 |
| Description | Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm ² PUR/PVC Cable, 10.0m (32.81') Length |
| IP Rating | IP67 |
| Product Family | Brad Micro-Change (M12) Connectors |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | Europe |
| Туре | Single Ended |
| UPC | 78172507805 |

Electrical

| Current - Maximum per Contact | 4.0A |
|-------------------------------|------------|
| Voltage - Maximum | 250V AC/DC |

Physical

| Cable Diameter | 5.70mm (.224") |
|---------------------------|---------------------|
| | |
| Cable Length | 10.0m (32.81') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Male-Pigtail |
| Кеуwау | Single |
| LED Indicator | No |
| Material - Cable Jacket | PUR/PVC |
| Material - Connector Body | PUR |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |

| Material - O-Ring | Fluoro-elastomer |
|-------------------------------|---------------------|
| Material - Plating Mating | Gold |
| Orientation | Straight to Pigtail |
| Poles | 5 |
| Temperature Range - Operating | -20° to +80°C |
| Wire/Cable Type | EU Cable |
| Wire Size (AWG) | N/A |

This document was generated on Jul 15, 2024