

Part Number : 1200652282

Series Number : 120065 Product Category : Circular Industrial Cordsets Product Description : Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut, 5 Poles, Male (Straight) to Pigtail, 22 AWG, Unshielded WSOR Cable, Green/Yellow 5th Wire, 10.0m (32.81') Length Status : Active

Engineering Number: 805006B42M100

Documents & Resources

Drawings Drawing 1200652282_sd.pdf

Specifications

Test Summary TS-120065-003-001.pdf

Product Environment Compliance

Compliance

| China RoHS | Not Reviewed |
|--------------------|--------------|
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Circular Industrial Cordsets |
| Series | 120065 |
| Description | Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut, 5 Poles, Male (Straight) to Pigtail, 22 AWG, Unshielded WSOR Cable, Green/Yellow 5th Wire, 10.0m (32.81') Length |
| IP Rating | IP67 |
| Product Family | Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | Europe |
| Туре | Single Ended |
| UPC | 887191554969 |

Agency

| | UL | E152210 |
|--|----|---------|
|--|----|---------|

Electrical

| Current - Maximum per Contact | 4.0A |
|-------------------------------|------|
| Voltage - Maximum | 60V |

Physical

| Cable Diameter | 5.50mm (.216") |
|----------------------|--------------------------|
| Cable Length | 10.0m (32.81') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Knurled Hexnut, Threaded |
| Gender | Male-Pigtail |
| Кеуwау | Single |

| No |
|---------------------|
| TPU |
| TPU |
| Brass |
| Nickel-plated Brass |
| Gold |
| Straight to Pigtail |
| 5 |
| -25° to +85°C |
| WSOR |
| 22 |
| |

This document was generated on Jul 16, 2024