

Part Number: 1200658746

Product Description: Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm² Black PUR LSOH Cable, 5.0m (16.40') Length

Series Number: 120065 Status: Active

Product Category: Circular Industrial Engineering Number: 805006H09M050

Cordsets

Documents & Resources

Drawings

Drawing 1200658746_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---------------------------------------------------|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category | Circular Industrial Cordsets |
| Series | 120065 |
| Description | Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm ² Black PUR LSOH Cable, 5.0m (16.40') Length |
| IP Rating | IP67 |
| Product Family | Brad Micro-Change (M12) Connectors |
| Product Name | Micro-Change (M12) |
| Region | Europe |
| Туре | Single Ended |
| UPC | 78172514689 |

Agency

| UL | E152210 |
|----|---------|
|----|---------|

Electrical

| Current - Maximum per Contact | 4.0A |
|-------------------------------|------|
| Voltage - Maximum | 60V |

Physical

| Cable Diameter | 5.80mm (.230") |
|---------------------------|--------------------|
| Cable Length | 5.0m (16.40') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Male-Pigtail |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | PUR |
| Material - Connector Body | PUR |

| Material - Contact | Copper Alloy |
|-------------------------------|---------------------|
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Net Weight | 193.600/g |
| Orientation | Straight to Pigtail |
| Poles | 5 |
| Temperature Range - Operating | -25° to +80°C |
| Wire/Cable Type | UL 21198 |
| Wire Size (AWG) | 22 |

This document was generated on Jul 16, 2024