



Part Number : 1200678465

Series Number : 120067

Product Category : Circular Industrial Cordsets

Product Description : Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut and PNP LED Sensors, 4 Poles, Female (Straight) to Pigtail, 22 AWG, Unshielded WSOR Cable, 3.0m (9.84') Length

Status : Active

Engineering Number : 8040P0B30M030

Documents & Resources

Drawings

Drawing 1200678465_sd.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|--------------|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|--|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120067 |
| Description | Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut and PNP LED Sensors, 4 Poles, Female (Straight) to Pigtail, 22 AWG, Unshielded WSOR Cable, 3.0m (9.84') Length |
| IP Rating | IP67 |
| Product Family | Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | Europe |
| Type | Single Ended |
| UPC | 889056091411 |

Electrical

| | |
|-------------------------------|-----------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 10-30V DC |

Physical

| | |
|---------------------------|--------------------------|
| Cable Diameter | 5.10mm (.201") |
| Cable Length | 3.0m (9.84') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Knurled Hexnut, Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | PNP Sensors |
| Material - Cable Jacket | TPU |
| Material - Connector Body | TPU |
| Material - Contact | Brass |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |

| | |
|-------------------------------|---------------------|
| Orientation | Straight to Pigtail |
| Poles | 4 |
| Temperature Range - Operating | -25° to +85°C |
| Wire/Cable Type | WSOR |
| Wire Size (AWG) | 22 |

This document was generated on Jul 16, 2024