



**Part Number :** 1200850004

**Series Number :** 120085

**Product Category :** Circular Industrial Connectors

**Product Description :** Ultra-Lock (M12) Single Keyway with PG7 Cable Fitting, Male, 5 Pole, Straight, Cable Diameter 3.30-6.60mm

**Status :** Active

**Engineering Number :** WA5006-31


Documents & Resources

Drawings

Drawing 1200850004\_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2022)9120-DC (17 Jan 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

## General

Status	Active
Category	Circular Industrial Connectors
Series	120085
Description	Ultra-Lock (M12) Single Keyway with PG7 Cable Fitting, Male, 5 Pole, Straight, Cable Diameter 3.30-6.60mm
Approvals	cCSAus certified
IP Rating	IP69K
Product Family	Brad Ultra-Lock Connection System
Product Name	Ultra-Lock (M12)
Type	Field Attachable Connector
UPC	78172553191

## Agency

CSA	LR6837
-----	--------

## Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC / 36V DC

## Physical

Cable Diameter	3.30-6.60mm (.130-.260")
Coupling Type	Push to Lock
Diagnostics / LEDs	No
Diagnostics Port	No
Gender	Male
Keyway	Single
Material - Connector Body	PA
Material - Contact	Brass
Material - Coupling Nut	Nickel-plated Brass
Material - Plating Mating	Gold
Net Weight	20.240/g
Orientation	Straight
Poles	5

Temperature Range - Operating	-25°C to +90°C
Wire Size (AWG)	18

---

This document was generated on Jul 16, 2024