

Part Number: 1200868115

Product Description: Nano-Change (M8) Single-Ended Cordset, 3 Poles, A-Coded, Female (Straight) to Pigtail, 0.25mm<sup>2</sup> Black PUR LSOH Cable, 10.0m (32.81') Length

Status: Active

Engineering Number: 403000H08M100

Series Number: 120086

**Product Category:** Circular Industrial

Cordsets

#### **Documents & Resources**

#### **Drawings**

Drawing 1200868115\_sd.pdf

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <u> </u>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Contains Lead per D(2023)3788-DC<br>(14 Jun 2023) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

#### **Part Details**

## General

| Status         | Active   |
|----------------|--|
| Category       | Circular Industrial Cordsets   |
| Series         | 120086   |
| Description    | Nano-Change (M8) Single-Ended<br>Cordset, 3 Poles, A-Coded, Female<br>(Straight) to Pigtail, 0.25mm <sup>2</sup> Black<br>PUR LSOH Cable, 10.0m (32.81')<br>Length |
| IP Rating      | IP67   |
| Product Family | Brad Nano-Change (M8) Products   |
| Product Name   | Nano-Change (M8)   |
| Protocol       | N/A  |
| Region         | Europe   |
| Туре           | Single Ended   |
| UPC            | 883906877002   |

## Electrical

| Current - Maximum per Contact | 3.0A            |
|-------------------------------|-----------------|
| Voltage - Maximum             | 60V AC / 75V DC |

# Physical

| 4.10mm (.161")      |
|---------------------|
| 10.0m (32.81')      |
| Black               |
| Nano-Change (M8)    |
| Pigtail             |
| Threaded            |
| Female-Pigtail      |
| A-Coded             |
| No                  |
| PUR                 |
| PUR                 |
| Copper Alloy        |
| Nickel-plated Brass |
| Fluoro-elastomer    |
|                     |

| Material - Plating Mating     | Gold                |
|-------------------------------|---------------------|
| Net Weight                    | 225.000/g           |
| Orientation                   | Straight to Pigtail |
| Poles                         | 3                   |
| Temperature Range - Operating | -25° to +80°C       |
| Wire/Cable Type               | UL 21198            |
| Wire Size (AWG)               | 24                  |

This document was generated on Jul 16, 2024