

Part Number: 1200868848

Product Description: Nano-Change (M8)
Single-Ended Cordset with Knurled Hexnut, 5
Poles B-Coded Female (90°) to Pigtail

Poles, B-Coded, Female (90°) to Pigtail, 0.25mm² Black PUR Cable, 1.0m (3.28') Length

Status: Active

Engineering Number: 405001H08M010

Series Number: 120086

Product Category: Circular Industrial

Cordsets

Documents & Resources

Drawings

Drawing 1200868848_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | Not Relevant |
| EU ELV | Compliant with Exemption 3 per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Contains Lead per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Circular Industrial Cordsets |
| Series | 120086 |
| Description | Nano-Change (M8) Single-Ended Cordset with Knurled Hexnut, 5 Poles, B-Coded, Female (90°) to Pigtail, 0.25mm ² Black PUR Cable, 1.0m (3.28') Length |
| IP Rating | IP67 |
| Product Family | Brad Nano-Change (M8) Products |
| Product Name | Nano-Change (M8) |
| Region | Europe |
| Туре | Single Ended |
| UPC | 191128974578 |

Electrical

| Current - Maximum per Contact | 3.0A |
|-------------------------------|-----------------|
| Voltage - Maximum | 30V AC / 36V DC |

Physical

| Cable Diameter | 4.70mm (.185") |
|---------------------------|---------------------|
| Cable Length | 1.0m (3.28') |
| Color - Cable Jacket | Black |
| Connector End A | Nano-Change (M8) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | B-Coded |
| LED Indicator | No |
| Material - Cable Jacket | PUR |
| Material - Connector Body | TPU |
| Material - Contact | Brass |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | FKM |

| Material - Plating Mating | Gold |
|-------------------------------|----------------|
| Net Weight | 222.000/g |
| Orientation | 90° to Pigtail |
| Poles | 5 |
| Temperature Range - Operating | -25° to +80°C |
| Wire/Cable Type | UL 21198 |
| Wire Size (AWG) | 24 |

This document was generated on Jul 16, 2024