



Part Number : 1200878463

Series Number : 120087

Product Category : Circular Industrial Cordsets

Product Description : Nano-Change (M8) to Micro-Change (M12) Double-Ended Cordset, 3 Poles, Female (Straight) to Male (Straight), 0.25mm² PVC Cable, 2.0m (6.56') Length

Status : Active

Engineering Number : 484030E02M020

Documents & Resources

Drawings

Drawing 1200878463_sd.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | Not Relevant |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Not Relevant |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|--|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120087 |
| Description | Nano-Change (M8) to Micro-Change (M12) Double-Ended Cordset, 3 Poles, Female (Straight) to Male (Straight), 0.25mm ² PVC Cable, 2.0m (6.56') Length |
| IP Rating | IP68 |
| Product Family | Brad Nano-Change (M8) Products |
| Product Name | Micro-Change (M12), Nano-Change (M8) |
| Protocol | N/A |
| Region | Europe |
| Type | Double Ended |
| UPC | 78172532419 |

Agency

| | |
|----|---------|
| UL | E152210 |
|----|---------|

Electrical

| | |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 60V AC / 75V DC |

Physical

| | |
|-------------------------|--------------------|
| Cable Diameter | N/A |
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Black |
| Connector End A | Nano-Change (M8) |
| Connector End B | Micro-Change (M12) |
| Coupling Style | Threaded |
| Gender | Female-Male |
| Keyway | None |
| LED Indicator | No |
| Material - Cable Jacket | PVC |

| | |
|-------------------------------|----------------------|
| Material - Connector Body | TPU |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 84.278/g |
| Orientation | Straight to Straight |
| Poles | 4 |
| Temperature Range - Operating | -30° TO +80°C |
| Wire/Cable Type | UL 2464 |
| Wire Size (AWG) | N/A |