

Part Number: 1201080243

Product Description: Micro-Change (M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 10.0m (32.81') Length

Status: Active

Engineering Number: E11A06011M100

Series Number: 120108

Product Category: Circular Industrial

Cordsets

Documents & Resources

Drawings

Drawing 1201080243_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | <u> </u> |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead; Lead monoxide per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------------|--|
| Category | Circular Industrial Cordsets |
| Series | 120108 |
| Description | Micro-Change (M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 10.0m (32.81') Length |
| IP Rating | IP67 |
| Performance Category | 5e |
| Product Family | Brad Industrial Ethernet Solutions |
| Product Name | Micro-Change (M12) |
| Region | America, Asia, Europe |
| Туре | Double Ended |
| UPC | 78172536917 |

Agency

| UL | E361772 |
|----|---------|

Electrical

| Current - Maximum per Contact | 1.5A |
|-------------------------------|------|
| Voltage - Maximum | 30V |

Physical

| Cable Diameter | 6.70mm (.264") |
|---------------------------|--------------------|
| Cable Length | 10.0m (32.81') |
| Color - Cable Jacket | Green |
| Connector End A | Micro-Change (M12) |
| Connector End B | Micro-Change (M12) |
| Coupling Style | Threaded |
| Gender | Male-Male |
| Keyway | D-Coded |
| LED Indicator | No |
| Material - Cable Jacket | PUR |
| Material - Connector Body | PUR |

| Material - Contact | Copper Alloy |
|-------------------------------|----------------------|
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Net Weight | 687.510/g |
| Orientation | Straight to Straight |
| Poles | 4 |
| Temperature Range - Operating | -20° to +60°C |
| Wire/Cable Type | Shielded PUR |
| Wire Size (AWG) | 22 |

This document was generated on Jul 16, 2024