

Part Number : 1203410922

Series Number : 120341 Product Category : Circular Industrial Cordsets Product Description : Micro-Change (M12) CAT6A Double-Ended Cordset, 8 Poles, X-Coded, Male (Straight) to Male (Straight), 26 AWG, Green Shielded PUR Cable, 25.0m (82.02') Length with ID Tag Status : Active Engineering Number : E22E06020M250H

#### **Documents & Resources**

#### Drawings

Drawing 1203410922\_sd.pdf

## **Product Environment Compliance**

#### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

## **Part Details**

General

Status	Active
Category	Circular Industrial Cordsets
Series	120341
Description	Micro-Change (M12) CAT6A Double- Ended Cordset, 8 Poles, X-Coded, Male (Straight) to Male (Straight), 26 AWG, Green Shielded PUR Cable, 25.0m (82.02') Length with ID Tag
IP Rating	IP67
Performance Category	6A
Product Family	Brad Industrial Ethernet Solutions
Product Name	Micro-Change (M12) Cat6A,Industrial Ethernet
Protocol	EtherNet
Region	America, Asia, Europe
Туре	Double Ended
UPC	193264551712

## Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	48V

# Physical

Cable Diameter	6.90mm (.272")
Cable Length	25.0m (82.02')
Color - Cable Jacket	Green
Connector End A	Micro-Change (M12)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Male-Male
Кеуwау	X-Coded
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	Brass
Material - Coupling Nut	Nickel-plated Brass

Material - Plating Mating	Gold
Net Weight	1126.679/g
Orientation	Straight to Straight
Poles	8
Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Shielded PUR
Wire Size (AWG)	26

This document was generated on Jul 16, 2024