

Part Number: 436400301

Product Description: Micro-Fit 3.0 Plug Housing, Single Row, 3 Circuits, UL 94V-0, Low-Halogen, Black

Series Number : 43640

Status: Active

**Product Category:** Connector Housings



#### **Documents & Resources**

### **Drawings**

436400301\_sd.pdf

#### 3D Models and Design Files

436400301\_stp.zip

#### **Specifications**

PK-43640-003-001.pdf

436500001-PS-JA-000.pdf

436500001-PS-KO-000.pdf

436500001-PS-SP-000.pdf

PS-43650-001.pdf

430450005-TS-000.pdf

430450007-TS-000.pdf

TS-43045-001-001.pdf

TS-43045-002-001.pdf

TS-43045-003-001.pdf

TS-46235-001-001.pdf

## **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>©</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Not Contained per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                          |

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

### **Part Details**

#### General

| Status       | Active  |
|--------------|---|
| Category     | Connector Housings  |
| Series       | 43640   |
| Description  | Micro-Fit 3.0 Plug Housing, Single<br>Row, 3 Circuits, UL 94V-0, Low-<br>Halogen, Black |
| Application  | Power, Wire-to-Wire   |
| Product Name | Micro-Fit 3.0   |
| UPC          | 800754951012  |

# Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

# **Physical**

| Circuits (maximum)    | 3     |
|-----------------------|-------|
| Color - Resin         | Black |
| Flammability          | 94V-0 |
| Gender                | Plug  |
| Glow-Wire Capable     | No    |
| Keying to Mating Part | None  |
| Lock to Mating Part   | Yes   |
| Material - Resin      | Nylon |

| Net Weight                    | 0.504/g        |
|-------------------------------|----------------|
| Number of Rows                | 1              |
| Packaging Type                | Bag            |
| Panel Mount                   | No             |
| Pitch - Mating Interface      | 3.00mm         |
| Polarized to Mating Part      | Yes            |
| Stackable                     | No             |
| Temperature Range - Operating | -40° to +105°C |

### **Solder Process Data**

| Lead-Free Process Capability | N/A                                     |
|------------------------------|---|
| Lead Tree Trocess capability | 1 |

## Mates With / Use With

# Mates with Part(s)

| Description   | Part Number   |
|---|---------------|
| Micro-Fit 3.0 Single Row Receptacle<br>Housings   | 43645         |
| Micro-Fit TPA-to-Micro-Fit TPA Off-<br>the-Shelf (OTS) Cable Assemblies                 | 145132        |
| Micro-Fit 3.0 Female-to-Micro-Fit<br>3.0 Female Off-the-Shelf (OTS)<br>Cable Assemblies | <u>214750</u> |
| Micro-Fit 3.0 Female-to-Pigtail Off-<br>the-Shelf (OTS) Cable Assemblies                | <u>214751</u> |

# Use with Part(s)

| Description  | Part Number   |
|--|---------------|
| Micro-Fit Male Crimp Terminals                               | <u>43031</u>  |
| Pre-Crimped Lead Micro-Fit 3.0<br>Male-to-Micro-Fit 3.0 Male | <u>214762</u> |
| Pre-Crimped Lead Micro-Fit 3.0<br>Male-to-Pigtail            | <u>214763</u> |